





ZS2000-2320 | M8 socket field assembly, sensor and power, IP 65/67

M8, socket, straight, female, 4-pin, A-coded

| Electrical data | |
|---------------------------------|--|
| Rated voltage | 30 V (according to IEC 61076-2-104) |
| Rated current | 4 A at 40 °C (according to IEC 61076-2-104) |
| Shielding | no |
| Insulation resistance | ≥ 100 MΩ (according to IEC 60512) |
| Mechanical data | |
| Installation size | M8 |
| Connector type | socket |
| Configuration | straight |
| Contact type | female |
| Number of positions (face) | 4-pin |
| Coding | A-coded |
| Wire termination | screw connection |
| Recommended torque, nut | 0.4 Nm |
| Mating cycles | ≥ 100 (according to IEC 60512-9a) |
| Way of locking | screw |
| Weight per piece | 0.028 kg (0.0617 lb) |
| Body colour | black |
| Body material | PA6 GF, UL 94 HB |
| Coupling nut material | CuZn, Ni |
| Seal | elastomers |
| O-ring | silicone/NBR |
| Contact carrier colour | black |
| Contact carrier material | PA 6, UL 94 V0 |
| Contact material | CuZn, Ni b/Au 0.2 gal. |
| Max. wire cross section | AWG20 (0.5 mm ²) |
| Max. cable outer diameter | 4 - 5.5 mm |
| Environmental data | |
| RoHS compliant | yes |
| Ambient temperature (operation) | -30...+85 °C, -22...+185 °F |
| Protection class | IP 65/67 in screwed condition (according to IEC 60529) |

Dimensions



| | |
|----|------------|
| A1 | 40.00 mm |
| A2 | Ø 14.00 mm |

Notes

- Illustrations similar

| Ordering information | |
|----------------------|--|
| ZS2000-2320 | Socket field assembly, Sensor and Power, IP 65/67, M8, straight, female, 4-pin, A-coded, 0.14...0.5 mm ² , Ø 4...5.5 mm |
| Accessories | |
| ZB8801-0000 | torque wrench for hexagonal plugs, adjustable |
| ZB8801-0002 | torque cable key, M12/wrench size 13, for ZB8801-0000 |

Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.