





ZS2000-2341 | M8 socket field assembly, sensor and power, IP 65/67

M8, socket, angled, female, 4-pin, A-coded

Electrical data	
Rated voltage	30 V (according to IEC 61076-2-104)
Rated current	4 A at 40 °C (according to IEC 61076-2-104)
Rated impulse voltage	0.8 kV
Shielding	no
Contact resistance	< 5 mΩ
Mechanical data	
Installation size	M8
Connector type	socket
Configuration	angled
Contact type	female
Number of positions (face)	4-pin
Coding	A-coded
Wire termination	solder connection
Recommended torque, nut	0.4 Nm
Mating cycles	≥ 100 (according to IEC 60512-9a)
Way of locking	screw
Body colour	black
Body material	PA UL 94 HB
Coupling nut material	CuZn, Ni
Contact carrier colour	black
Contact carrier material	TPU GF, UL 94
Contact plating	Au
Contact material	CuZn
Max. wire cross section	AWG24 (0.25 mm ²)
Max. cable outer diameter	3.5 - 5.0 mm
Environmental data	
RoHS compliant	yes
Ambient temperature (operation)	-40...+85 °C, -40...+185 °F
Protection class	IP 65/67 in screwed condition (according to IEC 60529)
Pollution level	3/2 (according to IEC 60664-1)

Dimensions



A1	28.50 mm
A2	Ø12.00 mm
A3	Ø 12.00 mm

Notes

- Illustrations similar

Ordering information	
ZS2000-2341	Socket field assembly, Sensor and Power, IP 65/67, M8, angled, female, 4-pin, A-coded, 0.14...0.25 mm ² , Ø 3.5...5 mm
Accessories	
ZB8800	torque wrench for M8 cables with knurl, incl. ratchet
ZB8800-0002	torque wrench key for M8 (for field assembly) for ZB8800

Beckhoff®, TwinCAT®, EtherCAT®, EtherCAT G®, EtherCAT G10®, EtherCAT P®, Safety over EtherCAT®, TwinSAFE®, XFC®, XTS® and XPlanar® are registered trademarks of and licensed by Beckhoff Automation GmbH. Other designations used in this publication may be trademarks whose use by third parties for their own purposes could violate the rights of the owners.

© Beckhoff Automation GmbH & Co. KG 02/2021

The information provided in this brochure contains merely general descriptions or characteristics of performance which in case of actual application do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.